



Paint

by hemway.

Premium Exterior Paint

A high opacity acrylic durable coating for exterior masonry.

Applications

- ✓ Exterior Walls
- ✓ Masonry Surfaces
- ✓ Fences
- ✓ Other Outdoor Surfaces

Features

- ✓ 12 Colours
- ✓ Matt
- ✓ Acrylic
- ✓ Water-Based
- ✓ Eco-Friendly
- ✓ High Pigmentation
- ✓ Vegan & Cruelty-Free
- ✓ Washable
- ✓ UV Resistant
- ✓ Non-Toxic

Preparation

Can be applied to most wood, metal and masonry without sanding or priming and directly over old paint and varnish. Ensuring your desired wood, metal or masonry is clean, free from wax, oil and fully dry. Carry out a sample test in a small area first to ensure it meets your expectations before carrying out your project.

Cleaning

Remove excess paint from used tools before washing. Wash brushes and rollers in warm soapy water. Replace lid firmly and store upright to avoid any spillage.

Important Instructions

- Read and follow SDS, TDS and label instructions.
- Stir all paints thoroughly before use.
- Always use the same batch number on the same job.
- Check colour and sheen. Hemway will not accept any discrepancies arising after use.
- Filter the product immediately before use.
- Reduce emissions and maintain quality by replacing tin lid after use.

Recommended Coats	1 - 2
Mixing	Ready For Use
Drying Time: Touch Dry	1 Hour at 20°C
Drying Time: Full Dry	24 Hours at 20°C
Recoatibility / Overcoating	1 Hour
Wet Film Thickness ¹	120 Microns
Dry Film Thickness ¹	80 Microns
Coverage	10m ² per L at 80µm DFT ¹
Flashpoint	N/A°C
Storage	Between 5°C and 25°C ²
Shelf Life	12 Months ³
Maximum VOC Content	0.012Kg/L
Regulations / Compliance	2004/42 IIA WB (A) 30
Colour Range	Hemway Colour Range

¹ Hemway Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the DFT stated in the agreed specification and to avoid areas of excessively low or high thickness.

² When not in use, cans must be kept sealed.

³ From delivery date, in original sealed containers.