



hemway.

**Sealant**  
by hemway.

## Declaration of Performance

**1. Unique identification code of the product-type:**

Hemway Premium Sealant & Adhesive All-In-One Colour Jet Black

**2. Intended use:**

EN 15651-1: F-EXT-INT-CC, Sealants for façade elements  
EN 15651-3: S, Sealants for sanitary joints  
EN 15651-4: PW-EXT-INT-CC, Sealants for pedestrian walkways

**3. Manufacturer:**

v1rtus Ltd T/A Hemway  
Unit N1 Gildersome Spur  
Leeds, LS27 7JZ

**4. System or systems of assessment and verification of constancy of performance (AVCP) as set out in Annex ZA:**

System 3 under Regulation (EU) No 305/2011:  
"SEALANTS FOR NON-STRUCTURAL USE IN JOINTS IN BUILDINGS AND FOOTPATHS"

**5. Harmonised standard:**

EN 15651-1:2012  
EN 15651-3:2012  
EN 15651-4:2012

Notified Body No. 0370, LGAI TECHNOLOGICAL CENTER, S. A./Applus,  
under the Construction Product Regulation No. 305/2011 for CE Marking; System 3

Notified Body No. 1292, FUNDACION TECNALIA RESEARCH & INNOVATION,  
under the Construction Product Regulation No. 305/2011 for CE Marking; System 3





Declaration of Performance

6. Declared performance:

EN 15651-1: F-EXT-INT-CC Non-structural sealant for façade elements of buildings Conditioning: Method A Substrates: Glass and Aluminium		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	NPD	EN 15651-1:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
<b>Water and Air Tightness</b>		
Resistance to Flow	≤ 3mm	
Loss of Volume	≤ 10%	
Tensile Properties: Elongation at Break	NF	
Durability	Pass	

EN 15651-3: S Non-structural sealant for sanitary joints Conditioning: Method A Substrates: Glass and Aluminium		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	NPD	EN 15651-3:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
<b>Water and Air Tightness</b>		
Resistance to Flow	≤ 3mm	
Loss of Volume	≤ 20%	
Tensile Properties: Elongation at Break	NF	
Microbiological Growth	XS3	
Durability	Pass	



Declaration of Performance

EN 15651-4: PW-EXT-INT-CC Non-structural sealant for pedestrian walkways Conditioning: Method A Substrates: Aluminium		
Essential Characteristic	Declared Performance	Harmonised Standard
Reaction to Fire (EN13501)	NPD	EN 15651-4:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
<b>Water and Air Tightness</b>		
Resistance to Flow	≤ 12mm	
Loss of Volume	≤ 10%	
Tensile Properties: Elongation at Break	NF	
Tear Resistance	NF	
Durability	Pass	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kristen Hemingway  
Managing Director  
v1rtus Ltd T/A Hemway

19.11.2024