CE

hemway.

Declaration of Performance

Sealant

1. Unique identification code of the product-type:

Hemway Premium Sealant & Adhesive All-In-One Colour

2. Intended use:

EN 15651-1:2012, Sealants for façade elements
EN 15651-3:2012, Sealants for sanitary joints
EN 15651-4:2012, Sealants for pedestrian walkways

3. Manufacturer:

v1rtus Ltd T/A Hemway
Unit N1 Gildersome Spur
Leeds, LS27 7JZ

4. System or systems of assessment and verification of constancy of performance (AVCP) as set out in Annex ZA.

System 3 under Regulation (EU) No 305/2011:
"SEALANTS FOR NON-STRUCTURAL USE IN JOINTS IN BUILDINGS AND FOOTPATHS"

5. Harmonised standard:

EN 15651-1:2012
EN 15651-3:2012
EN 15651-4:2012

Notified Body No. 0370, LGAI TECHNOLOGICAL CENTER, S. A./Applus,
under the Construction Product Regulation No. 305/2011 for CE Marking; System 3

Notified Body No. 1292, FUNDACION TECNALIA RESEARCH & INNOVATION,
under the Construction Product Regulation No. 305/2011 for CE Marking; System 3

6. Declared performance:

EN 15651-1:2012 Non-structural sealant for façade elements of buildings Conditioning: Method A Substrates: Glass, Aluminium and Mortar without primer		
Essential Characteristic	**Declared Performance**	**Harmonised Standard**
Reaction to Fire (EN13501)	-	EN 15651-1:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
Water and Air Tightness		
Resistance to Flow	≤ 3mm	
Loss of Volume	≤ 10%	
Tensile Properties: Elongation at Break	-	
Durability	-	

EN 15651-3:2012 Non-structural sealant for sanitary joints Conditioning: Method A Substrates: Glass, Aluminium and Mortar without primer		
Essential Characteristic	**Declared Performance**	**Harmonised Standard**
Reaction to Fire (EN13501)	-	EN 15651-3:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
Water and Air Tightness		
Resistance to Flow	≤ 3mm	
Loss of Volume	≤ 20%	
Tensile Properties: Elongation at Break	-	
Microbiological Growth	XS3	
Durability	-	

CE

hemway.

Declaration of Performance

Sealant

EN 15651-4:2012 Non-structural sealant for pedestrian walkways Conditioning: Method A Substrates: Glass, Aluminium and Mortar without primer		
Essential Characteristic	**Declared Performance**	**Harmonised Standard**
Reaction to Fire (EN13501)	-	EN 15651-4:2012
Release of Chemicals Dangerous to the Environment and Health	NPD	
Water and Air Tightness		
Resistance to Flow	-	
Loss of Volume	≤ 10%	
Tensile Properties: Elongation at Break	-	
Tear Resistance	-	
Durability	-	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Kristen Hemingway
Managing Director
v1rtus Ltd T/A Hemway

Aaron Quinn
Director
v1rtus Ltd T/A Hemway

19.11.2024